

MICRO SYSTEMS	OVATION 2i CDS 9000 WEB	OVATION 3 CDS 8120 ENC	OVATION 3 CDS 8000 iP	OVATION 2 CDS 7000 DEC	OVATION CDS 6680 USB
SPECIAL FEATURES					
Internet radio via v-tuner	•	-	-	-	-
Audio streaming (UPnP client)	•	-	-	-	-
iPhone/iPod docking station	-	-	•/•	-	-
USB / SD(HC) recording	-	•	•	-	-
AMPLIFIER UNIT					
PMPO	W 90	500	160	90	80
Music / nominal output	W 2 x 6 / 4 / 1 x 11/7	2 x 120 / 2 x 100 (4 ohms)	2 x 10/7 / 1 x 20/15	2 x 6 / 4 / 1 x 11/7	2 x 5 / 3 / 1 x 10/6
Dynamic Bass Boost / Ultra Bass System	•/-	•/-	•/-	•/-	•/-
Digital Sound Control	•	•	•	•	•
Preprogrammed EQ settings	5	5	5	5	5
Volume control digital	•	•	•	•	•
Wake-up function / Sleep function	•/•	•/•	•/•	•/•	•/•
TUNER UNIT					
Ranges	FM	FM	FM	FM, AM (MW)	FM, AM (MW)
PLL frequency synthesizer / Station memory	•/40	•/40	•/40	•/40	•/40
Radio Data System RDS / RDS radiotext	•/•	•/•	•/•	•/•	•/-
Programme type evaluation PTY	•	•	•	•	•
CD UNIT					
D/A converter	bit 1	1	1	1	1
Title memory	40	60	60	60	60
Shuffle (random play)	•	•	•	•	•
Can read CD-R / CD-RW	•/•	•/•	•/•	•/•	•/•
MP3 format	MPEG 1 layer 3, 44.1 kHz	MPEG 1 layer 3, 44.1 kHz	MPEG 1 layer 3, 44.1 kHz	MPEG 1 layer 3, 44.1 kHz	MPEG 1 layer 3, 44.1 kHz
WMA	•	•	•	•	•
Maximum folders / Maximum files	512	99 / 999	99 / 999	512	512
Data rate system	32 - 320 kbps, variable	32 - 320 kbps, variable	32 - 320 kbps, variable	32 - 320 kbps, variable	32 - 320 kbps, variable
ISO 9660 level 1 compatible	•	•	•	•	•
CASSETTE UNIT					
Automatic tone control	-	-	-	-	-
CD copy function	-	-	-	-	-
Transmission range	Hz -	-	-	-	-
CONNECTIONS					
WLAN	802.11b/g	-	-	-	-
LAN	RJ45 10/100 MBit	-	-	-	-
USB	•	•	•	•	•
SD, MMC slot	-	• (+ SDHC)	• (+ SDHC)	-	•
Line-, Aux in	•	•	•	•	•
75 ohms antenna coax.	•	•	•	•	•
Stereo headphones (3.5 mm)	•	•	•	•	•
Remote control / HiFi speakers (included)	•/ Magic Fidelity System	•/-	•/ Magic Fidelity System	•/ Magic Fidelity System	•/ Magic Fidelity System
MAINS UNIT					
Mains supply, mains frequency	V-, Hz 230, 50/60	230, 50/60	230, 50/60	230, 50/60	230, 50/60
Power consumption max. / stand-by	approx. W 28 / <6	340 / <1	23 / <1	39 / <2	35 / <2
DIMENSIONS					
Dimensions tower (W x H x D)	approx. cm 29.5 x 30 x 12.7	40 x 28 x 15.7	40 x 28 x 15.7	29.5 x 30 x 12.7	31 x 18 x 19
Dimensions speakers (W x H x D)	approx. cm built-in	not included in delivery	built-in	built-in	built-in

Technical data supplied without liability.

MICRO SYSTEMS	UMS 5810 WEB	UMS 4950 iP	UMS 4910 DEC	UMS 2020
SPECIAL FEATURES				
Internet radio via v-tuner	•	-	-	-
Audio streaming (UPnP client)	•	-	-	-
iPhone/iPod docking station	-	•/•	-	-
USB / SD(HC) recording	-	•	-	-
AMPLIFIER UNIT				
PMPO	W 360	65	65	32
Music / nominal output	W 2 x 45 / 30 (4 ohms)	2 x 8 / 5 (8 ohms)	2 x 8 / 5 (8 ohms)	2 x 4 / 2 (8 ohms)
Dynamic Bass Boost / Ultra Bass System	•/-	•/-	•/-	-/•
Digital Sound Control	•	•	•	•
Preprogrammed EQ settings	5	5	5	4
Volume control digital	•	•	•	•
Wake-up function / Sleep function	•/•	•/•	•/•	•/•
TUNER UNIT				
Ranges	FM, AM (MW)	FM	FM	FM, AM (MW)
PLL frequency synthesizer / Station memory	•/40	•/40	•/40	•/40
Radio Data System RDS / RDS radiotext	•/•	•/•	•/•	•/•
Programme type evaluation PTY	•	•	•	•
CD UNIT				
D/A converter	bit 16	1	1	1
Title memory	40	20	20	20
Shuffle (random play)	•	•	•	-
Can read CD-R / CD-RW	•/•	•/•	•/•	•/•
MP3 format	MPEG 1 layer 3, 44.1 kHz	MPEG 1 layer 3, 44.1 kHz	MPEG 1 layer 3, 44.1 kHz	MPEG 1 layer 3, 44.1 kHz
WMA	•	•	•	•
Maximum folders / Maximum files	256 / 511	99 / 999	99 / 999	99 / 999
Data rate system	32 - 320 kbps, variable	32 - 320 kbps, variable	32 - 320 kbps, variable	32 - 320 kbps, variable
ISO 9660 level 1 compatible	•	•	•	•
CASSETTE UNIT				
Automatic tone control	-	-	-	•
CD copy function	-	-	-	•
Transmission range	Hz -	-	-	125 - 8,000
CONNECTIONS				
WLAN	802.11b/g	-	-	-
LAN	RJ45 10/100 MBit	-	-	-
USB	•	•	•	•
SD, MMC slot	•	• (+ SDHC)	• (+ SDHC)	• (+ SDHC)
Line-, Aux in	•	•	•	•
75 ohms antenna coax.	•	•	•	-
Stereo headphones (3.5 mm)	•	•	•	•
Remote control / HiFi speakers (included)	•/ 2-way bass reflex	•/ 2-way bass reflex	•/ 2-way bass reflex	•/ bass reflex
MAINS UNIT				
Mains supply, mains frequency	V-, Hz 230, 50/60	230, 50/60	230, 50/60	230, 50/60
Power consumption max. / stand-by	approx. W 100 / <1	33 / <1	33 / <1	15 / <2
DIMENSIONS				
Dimensions tower (W x H x D)	approx. cm 16 x 25.5 x 26	15 x 23.7 x 23.5	15 x 23.7 x 23.5	15 x 23.2 x 20.3
Dimensions speakers (W x H x D)	approx. cm 16 x 25.5 x 24	14 x 23.7 x 20.5	14 x 23.7 x 20.5	15 x 23.2 x 20.3

Technical data supplied without liability.